REPLEX
PERI Panel Products

REPLEX is the economical recycled poplar panel and is applicable where secondary concrete finishes are required.

Application
- Slab formwork panel for concrete finishes with low requirements

Base board
- REPLEX is made of a selected recycled base panel with poplar faces

Bonding
- Moisture Resistant (MR) glue with 2 hours boiling test

Surface and edges
- Face and reverse: Dark brown or black phenolic film 180-200 g/m², depending on local availability
- Logo imprint: With "REPLEX" logo
- Edge treatment: Water resistant paint

Panel dimensions
- 1220/1250 x 2440/2500 mm

Nominal thicknesses
- 18 mm, 21 mm

Number of re-uses
- Typical number of re-uses is up to 3-5 times

The actual number of re-uses may vary depending on the application, type of use and handling. Please see additional our guide "PERI panel products – How to extend the lifetime of formwork plywood" or contact your local PERI panel manager.

Your benefits
- Poplar face veneers
- Other sizes and thicknesses on request

PERI SE
Formwork Scaffolding Engineering
Rudolf-Diesel-Strasse 19
89264 Weissenhorn, Germany
Phone +49 (0)7309.950-0
Fax +49 (0)7309.951-0
panels@peri.com
www.peri.com/en

Typographical mistakes reserved.
Attention: The given number of re-uses are non-binding guide values.

We reserve the right to amend specifications without notice or obligation.